CSCI 480 Computer Graphics Lecture 18

#### Global Illumination

Raytracing and Radiosity Subsurface Scattering Photon Mapping [Ch. 13.4-13.5]

March 28, 2012 Jernej Barbic University of Southern California

http://www-bcf.usc.edu/~jbarbic/cs480-s12/

## Global Illumination

- · Lighting based on the full scene
- · Lighting based on physics (optics)
- · Traditionally represented by two algorithms
  - Raytracing 1980Radiosity 1984
- More modern techniques include photon mapping and many variations of raytracing and radiosity ideas

Source: Dianne Hansford,

#### Direct Illumination vs. Global Illumination



- single (or few) bounces of the light only
- · for example, ray casting
- · no recursion (or shallow recursion only)
- fast lighting calculations based on light and normal vectors




- reflected, scattered and transmitted light
- many (infinite) number of bounces
- physically based light transport

#### Indirect Illumination



Color Bleeding

#### Soft Shadows



Shadows are much darker where the direct and indirect illuminations are occluded. Such shadows are important for "sitting" the sphere in the scene. They are difficult to fake without global illumination.

Caustics

- Transmitted light that refocuses on a surface, usually in a pretty pattern
- Not present with direct illumination





## Light Transport and Global Illumination

- · Diffuse to diffuse
- · Diffuse to specular
- · Specular to diffuse
- · Specular to specular
- Ray tracing (viewer dependent)
  - Light to diffuse
  - Specular to specular
- · Radiosity (viewer independent)
  - Diffuse to diffuse

7

#### Path Types

- OpenGL
  - L(D|S)E
- Ray Tracing
  - LDS\*E
- Radiosity
  - LD\*E
- · Path Tracing
  - attempts to trace
    "all rays" in a scene



8

# Images Rendered With Global Illumination









 Area light sources and soft shadows

9


#### Outline

- Direct and Indirect Illumination
- Bidirectional Reflectance Distribution Function
- Raytracing and Radiosity
- · Subsurface Scattering
- · Photon Mapping

10


# Solid Angle

- 2D angle subtended by object O from point x:
  - Length of projection onto unit circle at x
  - Measured in radians (0 to  $2\pi$ )
- 3D solid angle subtended by O from point x:
  - Area of of projection onto unit sphere at x
  - Measured in steradians (0 to  $4\pi$ )



# Light Emitted from a Surface

- Radiance (L): Power (φ) per unit area per unit solid angle
  - Measured in W / m<sup>2</sup>str
  - dA is projected area (perpendicular to given direction)








 $L = \frac{d\Phi}{dAd\omega}$ 

## Bidirectional Reflectance Distribution Function (BRDF)


If a ray hits a surface point at angle  $\omega_i$ , how much light bounces into the direction given by angle ω<sub>o</sub>?

It depends on the type of material.




#### Bidirectional Reflectance Distribution

- · General model of light reflection
- · Hemispherical function
- 6-dimensional (location, 4 angles, wavelength)



#### **BRDF Examples**


- · BRDF is a property of the material
- · There is no formula for most materials
- · Measure BRDFs for different materials (and store in a table)



#### Material Examples

A. Wilkie

Marschner et al. 2000



rig. 10. Resamples scattering diagrams to the BMT measurements of two paints: a blue enamel (top row) and a red automotive lacquer (bottom row). The RGB color measurements are shown from left to right.

## **BRDF** Isotropy

- · Rotation invariance of BRDF
- · Reduces 4 angles to 2
- · Holds for a wide variety of surfaces
- · Anisotropic materials
  - Brushed metal
  - Others?

#### Rendering Equation

 $\mathcal{L}(\mathbf{x},\omega) = \mathcal{E}(\mathbf{x},\omega) + \int f_r(\mathbf{x},\omega,\omega') G(\mathbf{x},\mathbf{x}') V(\mathbf{x},\mathbf{x}') \mathcal{L}(\mathbf{x}',\omega') dA'$ 

- ullet L is the radiance from a point on a surface in a given direction  $\omega$
- E is the emitted radiance from a point: E is non-zero only if x' is emissive
- V is the visibility term: 1 when the surfaces are unobstructed along the direction  $\omega$ , 0 otherwise
- G is the geometry term, which depends on the geometric relationship between the two surfaces x and x
- It includes contributions from light bounced many times off surfaces
- $f_r$  is the BRDF

#### Outline

- · Direct and Indirect Illumination
- · Bidirectional Reflectance Distribution Function
- · Raytracing and Radiosity
- · Subsurface Scattering
- · Photon Mapping

19


## Raytracing



From: http://jedi.ks.uiuc.edu/~johns/raytracer/raygallery/stills.html


20

# Raytracing



Albrecht Duerer, Underweysung der Messung mit dem Zirkel und Richtscheyt (Nurenberg, 1525), Book 3, figure 67.

# Raycasting vs. Raytracing







Raytracing

22

# Raytracing: Pros

- · Simple idea and nice results
- · Inter-object interaction possible
  - Shadows
  - Reflections
  - Refractions (light through glass, etc.)
- · Based on real-world lighting

Raytracing: Cons

- Slow
- Speed often highly scene-dependent
- Lighting effects tend to be abnormally sharp, without soft edges, unless more advanced techniques are used
- · Hard to put into hardware

24

## Supersampling I

- · Problem: Each pixel of the display represents one single ray
  - Aliasing
  - Unnaturally sharp images
- · Solution: Send multiple rays through each "pixel" and average the returned colors together

25

## Supersampling II

- Direct supersampling
  - Split each pixel into a grid and send rays through each grid point
- Adaptive supersampling
  - Split each pixel only if it's significantly different from its neighbors
- **Jittering** 
  - Send rays through randomly selected points within the pixel

26

#### The Radiosity Method




Cornell University

#### The Radiosity Method

- · Divide surfaces into patches (e.g., each triangle is one patch)
- Model light transfer between patches as system of linear equations
- · Important assumptions:
  - Diffuse reflection only
  - No specular reflection
  - No participating media (no fog)
  - No transmission (only opaque surfaces)
  - Radiosity is constant across each patch
  - Solve for R, G, B separately

28

# (Idealized) Radiosity Computation



#### Radiosity: Pros

- · Viewpoint independence means fast real-time display after initial calculation
- · Inter-object interaction possible
  - Soft shadows
  - Indirect lighting
  - Color bleeding
- Accurate simulation of energy transfer

## Radiosity: Cons

- Precomputation must be re-done if anything moves
- · Large computational and storage costs
- · Non-diffuse light not represented
  - Mirrors and shiny objects hard to include
- Lighting effects tend to be "blurry" (not sharp)
- · Not applicable to procedurally defined surfaces

31

#### Radiosity Equation

• For each patch i:  $B_i = E_i + \rho_i \sum_j (F_{ji}A_j/A_i)B_j$ 

$$= E_i + \rho_i \sum_i F_{ij} B_j$$

- Variables
  - B<sub>i</sub> = radiosity (unknown)
  - E<sub>i</sub> = emittance of light sources (given; some patches are light sources)
  - $\rho_i$  = reflectance (given)
  - F<sub>ij</sub> = form factor from i to j (computed) fraction of light emitted from patch i arriving at patch j
  - A<sub>i</sub> = area of patch i (computed)


32

#### The Form Factor

$$F_{ij} = \frac{1}{A} \iint \frac{V_{ij} \cos \phi_i \cos \phi_j}{\pi r^2} dA_j dA_i$$

 $F_{ii}$  is dimensionless

 $V_{ij}$  = 0 if occluded 1 if not occluded (visibility factor)



33

## Radiosity Example



Museum simulation. Program of Computer Graphics, Cornell University. 50,000 patches. Note indirect lighting from ceiling.

3/1


#### Outline

- · Direct and Indirect Illumination
- · Bidirectional Reflectance Distribution Function
- · Raytracing and Radiosity
- · Subsurface Scattering
- · Photon Mapping

Subsurface Scattering

- Translucent objects: skin, marble, milk
- · Light penetrates the object, scatters and exits
- · Important and popular in computer graphics

36




· Jensen et al. 2001



Using only BRDF

With subsurface light transport



#### Outline

- · Direct and Indirect Illumination
- · Bidirectional Reflectance Distribution Function
- · Raytracing and Radiosity
- · Subsurface Scattering
- · Photon Mapping

39

# **Photon Mapping**



From http://graphics.ucsd.edu/~henrik/images/global.html

40

## **Photon Mapping Basics**

- · Enhancement to raytracing
- · Can simulate caustics
- Can simulate diffuse inter-reflections (e.g., the "bleeding" of colored light from a red wall onto a white floor, giving the floor a reddish tint)
- · Can simulate clouds or smoke

**Photon Mapping** 

- "Photons" are emitted (raytraced) from light sources
- Photons either bounce or are absorbed
- Photons are stored in a photon map, with both position and incoming direction
- Photon map is decoupled from the geometry (often stored in a kd-tree)



Photon Map

42

#### **Photon Mapping**

- Raytracing step uses the closest N photons to each ray intersection and estimates the outgoing radiance
- Specular reflections can be done using "usual" raytracing to reduce the number of photons needed
- Numerous extensions to the idea to add more complex effects

43

#### Photon Mapping: Pros

- Preprocessing step is view independent, so only needs to be re-done if the lighting or positions of objects change
- · Inter-object interaction includes:
  - Shadows
  - Indirect lighting
  - Color bleeding
  - Highlights and reflections
  - Caustics current method of choice
- · Works for procedurally defined surfaces

44

#### **Photon Mapping: Cons**

- Still time-consuming, although not as bad as comparable results from pure raytracing
- Photon map not easy to update if small changes are made to the scene

45

## Photon Mapping Example



224,316 caustic photons, 3095 global photons

46

## Photon Mapping Example



47

#### Summary

- · Direct and Indirect Illumination
- · Bidirectional Reflectance Distribution Function
- Raytracing and Radiosity
- · Subsurface Scattering
- · Photon Mapping